

1. SPECIFICATIONS

2. DIMENSIONAL DRAWINGS

3. WIRING DIAGRAM

1. SPECIFICATIONS

• DIMENSIONS AND WEIGHTS

Type	S	L	SH	LH	SC	LC	SCH	LCH
Description code	BZBK				BZBF			
Overall length	410 mm (16.1 in)							
Overall width	280 mm (11.0 in)							
Overall height	945 mm (37.2 in)	1,100 mm (43.3 in)	945 mm (37.2 in)	1,100 mm (43.3 in)	945 mm (37.2 in)	1,100 mm (43.3 in)	945 mm (37.2 in)	1,100 mm (43.3 in)
Dry weight	12.1 kg (26.7 lb)	12.7 kg (28.0 lb)	12.4 kg (27.3 lb)	13.0 kg (28.7 lb)	12.4 kg (27.3 lb)	13.0 kg (28.7 lb)	12.7 kg (28.0 lb)	13.3 kg (29.3 lb)
Operating weight	13.1 kg (29.9 lb)	13.7 kg (30.2 lb)	13.4 kg (29.5 lb)	14.0 kg (30.9 lb)	13.4 kg (29.5 lb)	14.0 kg (30.9 lb)	13.7 kg (30.2 lb)	14.3 kg (31.5 lb)
Transom height	418 mm (16.5 in)	571 mm (22.5 in)	418 mm (16.5 in)	571 mm (22.5 in)	418 mm (16.5 in)	571 mm (22.5 in)	418 mm (16.5 in)	571 mm (22.5 in)
Transom angle	4-stage adjustment (5°, -10°, -15°, -20°)							
Tilt angle adjustment	1-stage adjustment							
Tilt-up angle	75°							
Swivel angle	360°							

• ENGINE

Type	Vertical 4-stroke, overhead valve single cylinder
Displacement	57 cm ³ (3.48 cu in)
Bore x stroke	45.0 x 36.0 mm (1.77 x 1.42 in)
Maximum horsepower	1.5 kW (2.0 PS) at 6,000 min ⁻¹ (rpm)
Maximum torque	2.69 N·m (0.27 kgf·m, 1.95 lbf·ft) at 4,500 min ⁻¹ (rpm)
Compression ratio	8.0 : 1
Fuel consumption	420 g/kW·h (309 g/PS·h, 0.68 lb/PS·h)
Cooling system	Forced air
Ignition system	Transistorized magneto ignition
Ignition timing	27° B.T.D.C.
Spark plug	NGK: CR5HSB, DENSO: U16FSR-UB
Carburetor	Float type
Lubrication system	Forced splash
Oil capacity	0.25 ℓ (0.26 US qt, 0.22 Imp qt)
Starting system	Recoil starter
Stopping system	Primary ground
Fuel used	Automotive unleaded gasoline 91 reach octane, 86 pump octane or higher
Fuel tank capacity	1.0 ℓ (0.26 US gal, 0.22 Imp gal)
Clutch	Centrifugal (SC, LC, SCH and LCH type only)